



NGL Innovator 240 MPSV Spec Sheet





NGL Innovator 240 MPSV Spec Sheet

Dimension and Regulatory Information

Length:	240'-0"	73.2 m
• Beam:	54'-0"	16.5 m
• Pot. water:	45,350 gal	172 m ³
• Fuel:	124,240 gal	470 m ³
• Water:	234,016 gal	886 m ³

IMO: 9251808 Flag: US

Certifications: Oceans-SOLAS, SIP, USCG Subchapter I, USCG Subchapter L

Classifications: Loadline, American Bureau of Shipping, +DPS-2, +A1, +AMS, OSV

Electronics

Auto Pilot, Beier IVCS 2000, C-Nav, CCTV Cameras, Depth Sounder, DGPS w/AIS, EPIRB, FanBeam, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radar (S-band), SARTs, Techsol, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

Special Features

- Knuckle Boom Crane: 1 x Hydra-Pro HPO240-21K
- Max Lift @ Max Radius: 7 MT @ 70 ft
- Max Lift @ Min Radius: 36 MT @ 20 ft
- Max Life @ Max Depth: 34 MT @ 1,100 ft
- Max Life @ Max Height: 20 MT @ 102 ft abv MD
- Personnel Rating: 1.5 MT
- Moon Pool: 36 in dia.
- Roll Damping: Anti-Roll Tank

